ALLIED AUTO



SPECIAL DEALS

Call us at (510)-656-6233

\$**1XQ**95

3/4 IN. DR. TORQUE WRENCH

Professional grade 3/4 dr reversible clicker type torque wrench. Measures from 100 to 600 ft-lbs in 1 pound increments . Torque wrench body engraved with ft-pound and newton-meters . Accuracy: 4% +- meets standards for torque wrenches . Heavy duty ABS storage and carrying case included.

M647


7 IN. HORIZONTAL

NGLE

OLISHER

M204

ANGLE POLISHER Powerful 1 HP motor with variable speed safety throttle. Hardened bevel gears provide extended life. Built-in air regulator for precise speed control. Handle mounts on either side for right or left hand operation. Contoured throttle control for easy handling. Includes 7" grinding wheel and metal blade guard.



direction rollers. Positive latching mechanism locks hose at desired length. Permanently lubricated all brass main shaft. Cold rolled steel with powder coated finish.



MV10



M619

5 IN. MULTI-PURPOSE VISE

Jaw width: 5". Jaw Opening: 4-1/2". Throat Depth: 2 1/4". Built in anvil: 3-11/32" x 3-3/4". 360 Degree swivel base. Heavy duty cast iron construction. Dual lock downs for easy positioning. Replaceable hardened steel jaws. Diamond serrated for a secure grip. Precision machined surface for flat shaping.

NULTI-PURPOSE

BENCH VISE

3/4 IN. DR. HEAVY DUTY IMPACT WRENCH

AIR IMPACT WRENCH

M627

5995

Powerful twin hammer clutch provides maximum torque and smooth operation. Generates up to 950ft/lbs of torque and 762 blows per minute. Built-in regulator with 3 forward and 3 reverse speeds. Socket retaining ring for rapid socket changes.

\$**149**95

Specifications: 3/4" Dr., Max Torque: 950 ft/ lbs, Working Torque: 75-450 ft/lbs, Free Speed RPM: 4,600, Standard Bolt Size: 1", Avg CFM, 7, Air Inlet NPT: 3/8", Weight: 10.7 lbs



Specifications: Free speed: 2500 RPM, Average CFM: 12, Spindle threat: 5/8-11, Air pressure: 90 PSI, Air inlet: 3//8" NPT, Hose size: 1/2" (D, Weight: 4.2 lbs

2000-WATT POWER INVERTER

Advanced technology features: Micro Computer Unit for precise output; improved transformer design better regulates temperature; more efficient heat dissipation extends life of the inverter. Converts vehicle power to a peak output of 4000W for use with small appliances and medium duty equipment. Features three standard 120V AC outlets and single 2.1A USB charging port. Three high-speed, built-in fans provide cool, constant operation. Digital display indicates battery voltage, output power in W or KW and error codes. Mounting rack to install unit on a flat area.









pressure test adapter, hose clamps and hose. GM throttle body injection (TBI) fuel pressure adapter, seals, tank valve, gasket, single & double end barbed hose adapter.

W89726 **Q**95

Includes adapters for most diesel engines including farm equipment.



designed for use with a breaker bar for additional torque. For use on your Ford, GM or Chrysler.

W89400



Prices valid from 2/1/21 - 3/31/21